



PET SHIELDING SYSTEMS

This extent of shielding calls for extensive expertise.

Because PET systems require a greater amount of shielding, you may want to rely on the impressive track record of NELCO PET installations.



A wide variety of medical facilities have put their trust in NELCO to manufacture and install comprehensive PET and PET/CT shielding systems. Specialized experience is essential, as the lead thickness for walls and ceilings can exceed 1". Heavier door systems require special consideration as well. NELCO can simply ship materials, supervise construction, or provide it all from design through finished construction.

FEATURES & HIGHLIGHTS

MANUFACTURING

Manufactured at 3 nationwide plants—
East Coast, West Coast, South

VERSATILITY

Can be used in new construction or
with facility renovation

DESIGN

In-house design personnel with
extensive PET expertise

QUALITY ASSURANCE

Impressive track record of widespread
PET installations

INSTALLATION

Experienced teams around the planet

SAFETY

Comprehensive safety programs for all
products and environments

SITE OPTIONS

- Lead-lined entry doors and frames
- Viewing window systems
- Utility shielding

TOP-LINE TECH SPECS

PRODUCT

PET Shielding Systems

USAGE

Low energy X-rays and gamma rays

PANELS

Lead-laminated, fire-treated plywood and drywall systems

BRICKS

NELCO N-Series interlocking lead brick systems

LEAD THICKNESS

As per physicists' requirements:

1/32"; 1/16"; 1/8"; 1/4"; 1/2"; 3/4"; 1"

(standard thicknesses—custom available)



Recycled materials
used in this product



NELCO
WORLDWIDE

Call 1-800-NELCO-13 (635-2613) or visit nelcoworldwide.com

REQUEST A QUOTE OR FOR ANY OF OUR INSPIRED SOUP-TO-NUT SERVICES INCLUDING: OCLLEN Consulting Services | Design & Build | Door Systems | Shielding Products

©2012 NELCO | All Rights Reserved 102612